

AC Millivolt Meter



FEATURES :

- * 300 mV Full scale sensitivity
- * Measures frequency from 10Hz ~ 1MHz
- * Measures from -70dB ~ +40dB in 12 ranges
- * Dual Channel (GVT-427B)

GVT-427B(2CH)/GVT-417B(1CH)

SPECIFICATIONS

INPUT	Voltage Range Decibel Range Accuracy Operating Mode Frequency Respones Impedance	300 mV~100V of Full Scale in 12 ranges -70dB ~ +40dB in 12 ranges ± 3% of full scale Channel 1 and 2 separately or simultaneously at channel 1 one channel only (GVT - 417B) 20Hz~200kHz ±3%, 10Hz~1MHz ±10% (reference 1 kHz) 1MW, approx, 40pF
OUTPUT	Level Distortion	Approx. 0.1Vrms at full scale Less than 2%
POWER SOURCE		AC 115/230V±10% , 50/60Hz
ACCESSORIES		Power cord x 1 Instruction Manual x 1 Test Lead GTL-101 x 2 (GTL-101 x 1 for GVT - 417B)
DIMENSIONS & WEIGHT		130(W) x 210(H)x295(D)mm; Approx. 2.7 kg

Note : CE mark is only for GVT-417B